

# Multi-Roll 44

Multi-Roll 44 is a lightweight, non-combustible mineral wool roll, designed to provide thermal and acoustic insulation in lofts. The roll can be used in any other application where a lightweight insulation is required and may be split to allow the user the choice of any of the three commonly required widths. Manufactured from recycled glass bottles, Multi-Roll 44 is strong, flexible and resilient.

IDEAL APPLICATION



LOFTS



## The benefits of Multi-Roll 44:

- Value for money - cost effective
- Thermal performance - K Value of 0.044W/mK
- Acoustic performance - excellent sound absorption
- Environmental - 84% recycled glass bottles, zero ODP & GWP, BRE Green Guide Rating A+ and HCFC & CFC Free
- Fire performance - Fire classification A1 non-combustible
- Easy-to-fit - simple installation process



## Product dimensions and information

THICKNESS mm	LENGTH m	WIDTH mm	AREA m <sup>2</sup>	R-VALUE m <sup>2</sup> /K/W	CODE
100	9.17	1200, 2x600, 3x400	11.00	2.25	5810
150	6.03	1160, 2x580, 3x386	7.00	3.40	5815
170	5.30	1160, 2x580, 3x386	6.15	3.85	5817
200	4.50	1160, 2x580, 3x386	5.22	4.50	5830

24 rolls per pallet

## U-Values

U-Value (W/m <sup>2</sup> K)	0.16	0.14	0.13
Thickness of insulation between joists (mm)	100	100	150
Thickness of insulation over joists (mm)	170	200	200

Typical U-Values achieved when using Multi-Roll 44 in a standard loft application

## ENVIRONMENTAL

Superglass products are made from natural materials and recycled glass. They are CFC and HCFC free, non-hygroscopic, will not rot, degrade or sustain vermin and will not encourage the growth of mould, bacteria or fungi. As well as having an exceptional recycled content all Superglass products are classified as having zero Ozone Depletion Potential (ODP) and zero Global Warming Potential (GWP).

## HEALTH & SAFETY

A COSHH and Material Safety Data Sheet can be obtained from Superglass Technical Team and also the Superglass website. Further reference can be made to MIMA's Health & Safety Statement which can be found at [www.mima.info](http://www.mima.info).

## BRITISH STANDARDS

Superglass products are manufactured to comply with the requirements of CE Marking 93/68/EEC and Technical European Harmonised Standards BS EN 13162:2008, BS EN 13172: 2012. Also manufactured in accordance with BSI Quality Assurance Standard BS EN ISO 9001: 2008.

## FIRE PERFORMANCE

Superglass products are classified as non-combustible with a Reaction to Fire Classification A1 when tested to BS EN 13501-1.

## VAPOUR RESISTANCE

Superglass products possess negligible vapour resistance allowing vapour to pass freely through the insulation.

## HANDLING & STORAGE

Superglass products are supplied compression packed in polythene to provide short term protection and for long term protection on site, the product must be stored indoors or under a waterproof covering in order to protect against weather damage.

## RIBA APPROVED CPD

An in depth look at Part L1A 2010 and its implications for new build housing. The CPD focuses on a 'fabric first' approach using mineral wool insulation and explores the effects of party wall thermal by-pass on the building envelope. This CPD also tackles issues raised by thermal bridging, looks at the myths and life cycle costs of glass mineral wool insulation as well as covering the green credentials of these products. Contact us by email [technical@superglass.co.uk](mailto:technical@superglass.co.uk) for more information.

## SUPERGLASS CERTIFICATION



FM02264



KM07767

**SUPERGLASS**  
Total Insulation Solutions

Superglass Insulation Limited  
Kerse Road, Thistle Industrial Estate, Stirling, Scotland FK7 7QQ

### TECHNICAL

Hotline: 0844 381 4022  
Email: [technical@superglass.co.uk](mailto:technical@superglass.co.uk)  
Fax: 01786 451245

### SALES

Tel: 01786 402013 / 01786 402014  
01786 402015 / 01786 402016  
Email: [sales@superglass.co.uk](mailto:sales@superglass.co.uk)  
Fax: 01786 451245



[www.superglass.co.uk](http://www.superglass.co.uk)

For further information, product sheets, alternative dimensions or facings please contact the Technical Hotline on 0844 381 4022.

Please note - all dimensions are nominal.

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.

